



Frame size	Rated output power	Rated current at	Full-load speed rpm	Full-load power factor	Full-load efficiency	Full-load torque	Starting current	Starting torque	Pull-out torque	Sound pressure level	Weight foot mounted
	P_N kW	230 V I_u A	n_N min^{-1}	$\cos \phi$	100% η %	M_N	(A)	M_s/M_N	M_k/M_N	dB(A) 1 metre (no load)	kg
AMAS-R 63K2	0.18	1.48	2800	0.92	60	0.063	5	0.40	1.7	70	3.9
AMAS-R 63G2	0.25	1.96	2800	0.92	63	0.087	7	0.40	1.7	70	4.4
AMAS-R 71K2	0.37	2.73	2800	0.92	67	0.129	10	0.35	1.7	75	6.2
AMAS-R 71G2	0.55	3.88	2800	0.92	70	0.195	15	0.35	1.7	75	6.5
AMAS-R 80K2	0.75	5.15	2800	0.92	72	0.258	20	0.33	1.7	75	8.3
AMAS-R 80G2	1.10	7.02	2800	0.95	75	0.366	30	0.33	1.7	78	11
AMAS-R 90S2	1.50	9.44	2800	0.95	76	0.513	45	0.3	1.7	83	15
AMAS-R 90L2	2.20	13.67	2800	0.95	77	0.752	65	0.3	1.7	83	17